

MARCH 2023



KNIGHTSHIELD

KS-6000

Walk-Pad, Non-Skid Granules

DESCRIPTION

KNIGHTSHIELD KS-6000 are crushed glass granules made from 100% post-consumer recycled glass.

USES

KNIGHTSHIELD KS-6000 is designed to be broadcast into the wet KNIGHTSHIELD KS-5200 to provide resistance to wear and improve traction under normal pedestrian traffic.

FEATURES/BENEFITS

- Environmentally friendly
- Skid-resistant
- Wear-resistant under pedestrian maintenance traffic
- Non-metallic
- Chemically inert

PACKAGING

1 Gal. (3.8 L Cans) (2 Cans/Carton)
5 Gal. (18.9 L) Pails

APPLICATION

Surface Preparation ... Prior to application, make sure the previous KNIGHTSHIELD coating is still wet to make sure granules imbed properly into coating.

Application Method ... Apply KNIGHTSHIELD KS-6000 walk-pad granules by broadcast method over the top of KNIGHTSHIELD KS-5200 silicone walk-pad (or alternate KNIGHTSHIELD coating) at a rate of 18 lb./100 ft.² (8.2 kg/9.3 m²).

Make sure to apply granules when the coating is still wet for proper adhesion of the granules to the coating. Avoid brushing/rolling over the granules, or applying an extra coat over the granules, as this can cause encapsulation of the granules and reduce or eliminate traction properties.

TECHNICAL DATA

Color	Multi/Green
Bulk Density	80 lb./ft. ³ (1.28 g/mL)
Solubility	Insoluble
Hardness	6 Mohs

LIMITATIONS/PRECAUTIONS

This product is intended for use only by professional applicators. Store in areas that are clean, dry and free of dust, dirt, and grease.

For most recent data sheet, LEED information and SDS, visit www.wrmeadows.com.

CONTINUED ON REVERSE SIDE ...



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.