

W. R. MEADOWS®

SEA[®]LIGHT™

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976

VAPOR
BARRIER
(IF REQ'D)

AIR-SHIELD LIQUID FLASHING (TO
SEAL AROUND MASONRY ANCHOR)

BRICK

EXTERIOR SHEATHING,
LGMF & BATT INSULATION

AIR-SHIELD SMP (MIN. 3" (76.2MM) OVERLAP)
(SEAL ALL PENETRATIONS & TERMINATE W/
AIR-SHIELD LIQUID FLASHING) (APPLY TO PRIMED
SURFACE)

WEEP BAFFLE

AIR-SHIELD THRU WALL FLASHING
(MIN. 6" (152.4MM) STRIP) (SEAL ALL
PENETRATIONS & TERMINATE W/ POINTING
MASTIC) (APPLY TO PRIMED SURFACE)

WEEP

LOOSE STEEL LINTEL

BACKER ROD & SEALANT

BACKER ROD & SEALANT

AIR-SHIELD SMP STRIP (6"
(152.4MM) STRIP) (EMBEDDED IN
AIR-SHIELD LIQUID FLASHING) (SEAL
ALL PENETRATIONS W/ AIR-SHIELD
LIQUID FLASHING) (APPLY TO
PRIMED SURFACE)

SPRAY POLYURETHANE FOAM
SEALANT OR ROCK WOOL/
MINERAL WOOL W/ BACKER
ROD & SEALANT

NOTE:DETAIL IS DESIGNED TO
BE A GUIDE FOR W. R. MEADOWS
INSTALLATION PURPOSES ONLY

TITLE:

AIR-SHIELD SMP LGMF BU LOOSE LINTEL WINDOW HEAD

SCALE:

NTS

DATE:

AUG 24, 2018