



ROOF FLASHING

ROOF MEMBRANE

ROOF COUNTER FLASHING

VAPOR BARRIER (IF REQ'D)

AIR-SHIELD TRANSITION MEMBRANE  
(MIN. 3" (76.2MM) OVERLAP) (SEAL ALL PENETRATIONS W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BACKER ROD BELLOW FOR DEFLECTION)

AIR-SHIELD LSR (75 MILS WET)  
(MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

PRE-INSTALLED MASONRY ANCHOR  
(SEALED W/ AIR-SHIELD LSR)

BOND BEAM CMU

INSULATED CMU

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

**W. R. MEADOWS INC.**  
 300 INDUSTRIAL DR.  
 HAMPSHIRE, IL 60140-0338  
 1-800-342-5976



TITLE: **AIR-SHIELD LSR CMU BU ANGLED ROOF TIE-IN  
(EXTERIOR BRICK WALL) (NO INSULATION)**

SCALE: **NTS**  
 DWG NO.: **N/A**  
 DATE: **JUNE 11, 2021**