

AIR-SHIELD LSR (75 MILS WET) (MIN. 3" (76.2mm)
OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

AIR-SHIELD LIQUID FLASHING (12-15 MILS SPREAD
EVENLY) (MIN. 2" (50.8mm) EXTENDED ONTO SURFACES)

EXTERIOR BRICK WALL

INSULATED CMU BU

PRE-INSTALLED MASONRY ANCHOR
(SEALED W/ AIR-SHIELD LSR)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST
BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.
MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976

W. R. MEADOWS

SEALTIGHT

TITLE: AIR-SHIELD LSR CMU BU EXTERNAL CORNER (AIR-SHIELD LF)
(EXTERIOR BRICK WALL) (NO INSULATION) (PLANVIEW)

SCALE: DWG NO.:

NTS N/A

DATE: JULY 6, 2021