

INSULATED CMU BU

EXTERIOR BRICK WALL

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LSR)

AIR-SHIELD LSR (75 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976

W. R. MEADOWS

SEALTIGHT

TITLE:

AIR-SHIELD LSR CMU BU INTERNAL CORNER
(EXTERIOR BRICK WALL) (NO INSULATION) (PLANVIEW)

SCALE: DWG NO.:

NTS N/A

DATE: JULY 7, 2021