



- PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LSR)
- INSULATED CMU BU
- AIR-SHIELD LSR (75 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)
- AIR-SHIELD THRU WALL FLASHING (MIN. 6" (152.4MM) STRIP) (SEAL ALL PENETRATIONS & TERMINATE W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE)
- WEEP
- WEEP BAFFLE
- LOOSE STEEL LINTEL
- AIR-SHIELD LIQUID FLASHING (12-15 MILS SPREAD EVENLY) ( MIN. 2" (50.8mm) EXTENDED ONTO SURFACES)
- ALUMINUM WINDOW

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE: AIR-SHIELD LSR CMU BU LOOSE LINTEL WINDOW HEAD 2  
(AIR-SHIELD LF) (EXTERIOR BRICK WALL) (NO INSULATION)

SCALE: NTS  
DATE: JUNE 9, 2021

DWG NO.: N/A