

ROOF MEMBRANE

ROOF CAP FLASHING

AIR-SHIELD TRANSITION MEMBRANE
(MIN. 3" (76.2MM) TURNED DOWN WALL) (SEAL
ALL PENETRATIONS W/ POINTING MASTIC)
(APPLY TO PRIMED SURFACE)

AIR-SHIELD LSR (75 MILS WET) (APPLY
TO PROPERLY PREPARED SUBSTRATE)

BOND BEAM CMU

INSULATED CMU

MASONRY ANCHOR
(SEALED W/ POINTING MASTIC)

POINTING MASTIC (TO SEAL
AROUND MASONRY ANCHOR)

EXTERIOR BRICK WALL

RIGID INSULATION (IF REQ'D)

AIR-SHIELD TRANSITION MEMBRANE (12"
(304.8mm) STRIP) (SEAL ALL PENETRATIONS W/
POINTING MASTIC) (APPLY TO PRIMED SURFACE)

AIR-SHIELD TRANSITION MEMBRANE
(MIN. 6" (152.4mm) STRIP) (SEAL ALL
PENETRATIONS W/ BEAD OF POINTING MASTIC)
(APPLY TO PRIMED SURFACE) (BELLOWED W/
BACKER ROD & COMPRESSIBLE FILLER)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST
BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.
MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE:

AIR-SHIELD LSR CMU BU ROOF TIE-IN @ PARAPET
(EXTERIOR BRICK WALL) (INSULATION)

SCALE: DWG NO.:
NTS N/A
DATE: JULY 7, 2021