

ROOF MEMBRANE

ROOF CAP FLASHING

AIR-SHIELD TRANSITION MEMBRANE
 (MIN. 3" (76.2MM) TURNED DOWN WALL) (SEAL
 ALL PENETRATIONS W/ POINTING MASTIC)
 (APPLY TO PRIMED SURFACE)

POINTING MASTIC (TO SEAL AIR-SHIELD)

AIR-SHIELD LSR (75 MILS WET) (APPLY
 TO PROPERLY PREPARED SUBSTRATE)

BOND BEAM CMU

INSULATED CMU

PRE-INSTALLED MASONRY ANCHOR
 (SEALED W/ AIR-SHIELD LSR)

EXTERIOR BRICK WALL

AIR-SHIELD TRANSITION MEMBRANE (12"
 (304.8mm) STRIP) (SEAL ALL PENETRATIONS W/
 POINTING MASTIC) (APPLY TO PRIMED SURFACE)

AIR-SHIELD TRANSITION MEMBRANE
 (MIN. 6" (152.4mm) STRIP) (SEAL ALL
 PENETRATIONS W/ BEAD OF POINTING MASTIC)
 (APPLY TO PRIMED SURFACE) (BELLOWED W/
 BACKER ROD & COMPRESSIBLE FILLER)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST
 BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.
 MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE:

**AIR-SHIELD LSR CMU BU ROOF TIE-IN @ PARAPET
 (EXTERIOR BRICK WALL) (NO INSULATION)**

SCALE: DWG NO.:
 NTS N/A
 DATE: JUNE 11, 2021