



INSULATED CMU BLOCK

RIGID INSULATION (IF REQ'D)

EXTERIOR BRICK WALL

AIR-SHIELD LSR (75 MILS WET)
 (MIN. 3" (76.2mm) OVERLAP) (APPLY TO
 PROPERLY PREPARED SUBSTRATE)

AIR-SHIELD THRU WALL FLASHING (SEAL
 ALL PENETRATIONS W/ BEAD OF POINTING
 MASTIC) (APPLY TO PRIMED SURFACE)

WEEP BAFFLE

COVE OF BEM

WEEP

DRIP EDGE

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE:

AIR-SHIELD LSR CMU BU WALL BASE ABOVE
 GRADE (EXTERIOR BRICK WALL) (INSULATION)

SCALE: DWG NO.:
 NTS N/A
 DATE: AUG 20, 2017