



ALUMINUM WINDOW

BACKER ROD & SEALANT

AIR-SHIELD LIQUID FLASHING (12-15 MILS SPREAD EVENLY) (MIN. 2" (50.8mm) EXTENDED INTO ROUGH OPENING)

AIR-SHIELD LSR (75 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LSR)

EXTERIOR BRICK WALL

INSULATED CMU BLOCK

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE:

AIR-SHIELD LSR CMU BU WINDOW SILL (AIR-SHIELD LF)
(EXTERIOR BRICK WALL) (NO INSULATION)

SCALE:

NTS

DATE:

DWG NO.:

N/A

JUNE 9, 2021