



ALUMINUM WINDOW

BACKER ROD & SEALANT

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

AIR-SHIELD LSR (75 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

MASONRY ANCHOR (SEALED W/ POINTING MASTIC)

POINTING MASTIC (TO SEAL AROUND MASONRY ANCHOR)

INSULATED CMU BLOCK

RIGID INSULATION (IF REQ'D)

EXTERIOR BRICK WALL

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.