



- CEM-KOTE FLEX ST (2ND LAYER 31.5 MILS)
- CEM-KOTE FLEX ST (1ST LAYER 31.5 MILS) (APPLIED TO PROPERLY PREPARED SURFACE)
- CEM-KOTE FLEX ST (DETAIL LAYER) (2ND LAYER 31.5 MILS)
- REINFORCING FABRIC HD (12" (304.8mm) STRIP CENTERED) (EMBEDDED IN CEM-KOTE FLEX ST)
- CEM-KOTE FLEX ST (DETAIL LAYER) (1ST LAYER 31.5 MILS) (APPLIED TO PROPERLY PREPARED SURFACE)
- MEADOW-CRETE OV (2" x 2" (50.8mm x 50.8mm) - 2½" x 2½" (63.5mm x 63.5mm) COVE) (APPLY TO PROPERLY PREPARED & SOUND SUBSTRATE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.