



CEM-KOTE FLEX ST (2ND LAYER 31.5 MILS)
(APPLIED TO PROPERLY PREPARED SURFACE)

CEM-KOTE FLEX ST (1ST LAYER 31.5 MILS)
(APPLIED TO PROPERLY PREPARED SURFACE)

CEM-KOTE FLEX ST (63 MILS) (DETAILING LAYER)
(APPLIED TO PROPERLY PREPARED SURFACE)

MEADOW-CRETE OV (2" x 2" (50.8mm x 50.8mm)
- 2½" x 2½" (63.5mm x 63.5mm) COVE) (APPLY TO WET
EDGE FIBRE-PRIME & SOUND SUBSTRATE)

STEEL PIPE

EXISTING- REMOVE ALL RUST BEFORE APPLICATION.

NEW- CLEAN WITH TSP SOLUTION TO REMOVE ANY
OIL RESIDUE (TEST BOND OF FIBRE-PRIME IF UNSURE)

PAINTED- ABRABE USING SAND PAPER AND
PRESSURE WASH DUST AWAY

FIBRE-PRIME (FOR PROPER BOND) (APPLY TO
PROPERLY PREPARED & SOUND SUBSTRATE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.