



PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2ND LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1ST LAYER 90 MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

HRM 714 (125MILS DETAILING LAYER) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

NEOPRENE FLASHING MEMBRANE (MIN. 6" (152.4mm) STRIP CENTERED)

HRM 714 (1ST LAYER 90 MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

REINFORCING FABRIC HCR

HRM 714 (2ND LAYER 125MILS)

MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

DETAILING NOTE:
1) MECHANICAL FASTENING OF THE TOP LEADING EDGE OF MODIFIED ASPHALT OR PROTECTION COURES FOR VERTICAL APPLICATION IS RECOMMENDED.

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.
300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976



TITLE: **HRM 714 TRANSITION @ OUTSIDE CORNER EDGE (NEOPRENE) (MEL-DRAIN) (NO INSULATION)**

SCALE: **NTS**
DATE: **MAY 6, 2021**
DWG NO.: **HRM714-14**