



PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2ND LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1ST LAYER 90MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

BED OF BEM SEALANT (FOR BOND TO SUBSTRATE), HYDRALASTIC 836 (60 MILS) (DETAILING LAYER) (APPLY TO PROPERLY PREPARED SUBSTRATE), MEL-ROL 2-COMPONENT (90 MILS) OR HRM 714 (90 MILS)

HYDRASTOP SA (FABRIC FACING CONCRETE) (MIN. 12" (304.8mm) TURNED OVER EDGE) (EMBEDDED IN MEL-ROL TWO-COMPONENT OR HYDRALASTIC 836) (SEAL PENETRATIONS W/ MEL-ROL TWO-COMPONENT OR HYDRALASTIC 836)

MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

WOOD LAGGING

DETAILING NOTE:
1) IN ADDITION TO THIS DETAIL, REFER TO HYDRASTOP SA INSTALLATION GUIDELINES.

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.