



PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2ND LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1ST LAYER 90 MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

DETAIL STRIP OR MEL-ROL STRIP (MIN. 12" (304.8mm) STRIP CENTERED) (TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

MEL-ROL LM (60 MILS WET) (APPLY TO PROPERLY PREPARED SUBSTRATE)

POINTING MASTIC (TO SEAL MEL-ROL)

MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

DETAILING NOTES:
 1) SCORCH & REMOVE THE TOP POLYFILM OF MEL-ROL TO EXPOSE THE UNDERLYING SBS ASPHALT IMMEDIATELY PRIOR TO APPLYING THE HRM 714 SYSTEM.

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.
 300 INDUSTRIAL DR.
 HAMPSHIRE, IL 60140-0338
 1-800-342-5976



TITLE: **HRM 714 TRANSITION FROM MEL-ROL LM @ OUTSIDE CORNER EDGE (MEL-DRAIN)**

SCALE: **NTS**
 DATE: **NOV 30, 2022**
 DWG NO.: **HRM714-27**