



PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2<sup>ND</sup> LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1<sup>ST</sup> LAYER 90MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

BED OF BEM SEALANT (FOR BOND TO SUBSTRATE), HYDRALASTIC 836 (60 MILS) (DETAILING LAYER) (APPLY TO PROPERLY PREPARED SUBSTRATE), MEL-ROL 2-COMPONENT (90 MILS) OR HRM 714 (90 MILS)

PRECON (FABRIC FACING CONCRETE) (MIN. 6" (152.4mm) TURNED UP WALL) (EMBEDDED IN HYDRALASTIC 836, BEM, POINTING MASTIC OR HRM 714) (TERMINATE W/ TERM BAR & HYDRALASTIC 836, BEM, POINTING MASTIC OR HRM 714)

MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

WOOD LAGGING

**DETAILING NOTE:**  
1) IN ADDITION TO THIS DETAIL, REFER TO PRECON INSTALLATION GUIDELINES.

**NOTE:** DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.