



HRM 714 (125MILS DETAILING LAYER) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

NEOPRENE FLASHING MEMBRANE (MIN. 6" (152.4mm) STRIP CENTERED)

PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2<sup>ND</sup> LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1<sup>ST</sup> LAYER 90MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

**DETAILING NOTE:**  
 1) ROLLED MEL-ROL DETAIL STRIP IS AN ACCEPTABLE FLASHING ALTERNATE TO NEOPRENE.  
 2) OPTIONAL USE OF A STAINLESS STEEL BAND CLAMP AT THE END OF NEOPRENE OR MEL-ROL DETAIL STRIP IS SUGGESTED TO PROVIDE A MORE ROBUST TERMINATION.

**NOTE:** DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.