



POINTING MASTIC (TO SEAL COUNTER FLASHING)

POINTING MASTIC (TO SEAL HRM 714 SYSTEM)

PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2<sup>ND</sup> LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1<sup>ST</sup> LAYER 90MILS) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

**DETAILING NOTE:**

1) WHERE VERTICAL TERMINATION IS EXPOSED TO UV CONDITIONS, NEOPRENE FLASHING MEMBRANE OR GRANULAR COATED MODIFIED ASPHALT PROTECTION COURSE SHALL BE USED.

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

**W. R. MEADOWS INC.**

300 INDUSTRIAL DR.  
HAMPSHIRE, IL 60140-0338  
1-800-342-5976



TITLE:

HRM 714- VERTICAL TERMINATION @ REGLET (NO INSULATION)

SCALE:

NTS

DATE:

AUG 10, 2021

DWG NO.:

HRM714-21