



TERM BAR & POINTING MASTIC (TO SEAL HRM 714 SYSTEM)

PROTECTION COURSE OR MODIFIED ASPHALT

HRM 714 (2ND LAYER 125MILS)

REINFORCING FABRIC HCR

HRM 714 (1ST LAYER 90 MILS) (APPLY TO PROPERLY PREPARED & PRIMED SUBSTRATE)

DETAILING NOTE:

1) WHERE VERTICAL TERMINATION IS EXPOSED TO UV CONDITIONS, NEOPRENE FLASHING MEMBRANE OR GRANULAR COATED MODIFIED ASPHALT PROTECTION COURSE SHALL BE USED.

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976



TITLE:

HRM 714- VERTICAL TERMINATION (NO INSULATION)

SCALE:

NTS

DATE:

AUG 10, 2021

DWG NO.:

HRM714-20