



AIR-SHIELD THRU WALL FLASHING (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

POINTING MASTIC (TO SEAL AIR-SHIELD)

RIGID INSULATION (IF REQ'D)

MEL-ROL LM (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

DETAIL STRIP OR MEL-ROL STRIP (EXTEND MIN. 4½" (114.3mm) UP WALL) (TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

COVE OF BEM SEALANT (FOR TRANSITION) (TO SEAL JOINT)

DETAIL STRIP OR MEL-ROL STRIP (EXTEND MIN. 4½" (114.3mm) DOWN WALL) (TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

MEL-ROL LM (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE:

MEL-ROL LM @ BASE OF BASE OF WALL TRANSITION TO AIR-SHIELD

SCALE:

NTS

DWG NO.:

N/A

DATE:

JUNE 16, 2022