



MEL-DRAIN (FABRIC FACING EARTH)
(TERMINATE W/ TERM BAR IF REQ'D)

MEL-ROL LM (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP)
(APPLY TO PROPERLY PREPARED SUBSTRATE)

DETAIL STRIP OR MEL-ROL STRIP (EXTEND MIN. 4½" (114.3mm) UP WALL)
(MIN. 6" (152.4mm) TURNED DOWN PRECON) (TERMINATE W/ BEAD OF POINTING
MASTIC IF REQ'D) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

COVE OF BEM SEALANT (FOR TRANSITION)

DETAIL STRIP OR MEL-ROL STRIP (EXTEND
MIN. 4½" (114.3mm) UP WALL) (MIN. 6" (152.4mm)
TURNED DOWN PRECON) (TERMINATE W/ BEAD OF
POINTING MASTIC IF REQ'D) (APPLY MEL-PRIME TO
SURFACE PRIOR TO APPLICATION)

MEL-ROL LM (60 MILS WET) (APPLY
TO PROPERLY PREPARED SUBSTRATE)

WATERSTOP EC

MUD SLAB

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST
BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.
MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

