

W. R. MEADOWS

SEALTIGHT

W. R. MEADOWS INC.

300 INDUSTRIAL DR.  
HAMPSHIRE, IL 60140-0338  
1-800-342-5976

MEL-ROL LM (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP)  
(APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

BACKER ROD

DETAIL STRIP OR MEL-ROL STRIP (EXTEND MIN. 3"  
(76.2mm) ONTO PENETRATION) (MIN. 6" (152.4mm) STRIP)  
(TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D)  
(APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

POINTING MASTIC (TO SEAL MEL-ROL)

MEL-DRAIN W/ FILTER FABRIC (FABRIC  
FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

RIGID INSULATION (IF REQ'D)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST  
BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.  
MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

TITLE:

MEL-ROL LM VERTICAL PENETRATION (INSULATION) (CMU)

SCALE: DWG NO.:

NTS N/A

DATE:

MAY 4, 2021