



POINTING MASTIC (TO SEAL MEL-ROL)

MEL-DRAIN (FABRIC FACING EARTH)  
(TERMINATE W/ TERM BAR IF REQ'D)

RIGID INSULATION (IF REQ'D)

WATERSTOP EC

MEL-ROL 2-COMPONENT (90 MILS)

PREMOULDED MEMBRANE VAPOR SEAL W/  
PLASMATIC CORE (PMPC) (EMBEDDED IN MEL-ROL  
2-COMPONENT) (EXTEND TURN UP MIN. 3" (76.2mm)  
PASS JOINT) (TERMINATE W/ PMPC TAPE IF REQ'D)

MEL-ROL (APPLY MEL-PRIME TO SURFACE PRIOR  
TO APPLICATION) (TERMINATE W/ TERM BAR & BEAD  
OF POINTING MASTIC IF REQ'D)

MEL-ROL 2-COMPONENT (90 MILS)

PREMOULDED MEMBRANE VAPOR SEAL  
W/ PLASMATIC CORE (PMPC) (EMBEDDED  
IN MEL-ROL 2-COMPONENT) (BUTTED AGAINST  
REBAR) (TERMINATE W/ PMPC TAPE IF REQ'D)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.