

AIR-SHIELD LMP (60 MILS WET)
(MIN. 3" (76.2mm) OVERLAP) (APPLY TO
PROPERLY PREPARED SUBSTRATE)

AIR-SHIELD TRANSITION MEMBRANE
(MIN. 6" (152.4mm) STRIP CENTERED) (SEAL
ALL PENETRATIONS W/ BEAD OF POINTING
MASTIC) (APPLY TO PRIMED SURFACE)

EXTERIOR STONE WALL

INSULATED CMU BLOCK

PRE-INSTALLED MASONRY ANCHOR
(SEALED W/ AIR-SHIELD LMP)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST
BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.
MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976



TITLE:

AIR-SHIELD LMP CMU BU EXTERNAL CORNER
(EXTERIOR STONE WALL) (NO INSUL) (PLANVIEW)

SCALE: DWG NO.:
NTS AS_LMP-86
DATE: MAY 4, 2022