



PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LMP)

INSULATED CMU BLOCK

AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

AIR-SHIELD THRU WALL FLASHING (MIN. 6" (152.4MM) STRIP) (SEAL ALL PENETRATIONS & TERMINATE W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE)

WEEP

WEEP BAFFLE

LOOSE STEEL LINTEL

AIR-SHIELD THRU WALL FLASHING (MIN. 6" (152.4MM) STRIP CENTERED) (SEAL ALL PENETRATIONS & TERMINATE W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE)

ALUMINUM WINDOW

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.