



INSULATED CMU BLOCK

AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

EXTERIOR BRICK WALL

AIR-SHIELD THRU WALL FLASHING (MIN. 12" (304.8mm) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

WEEP BAFFLE

WEEP, METAL DRIP EDGE COUNTER FLASHING

BACKER ROD & COMPRESSIBLE FILLER

HUNG LINTEL SYSTEM FILL JTS IN SYSTEM W/ SPF SEALANT TO TRANSITION AVB (SEMI RIGID FILL @ SHIM SPACE BEHIND LINTEL TO SUPPORT FLASHING)

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOWED W/ BACKER ROD & COMPRESSIBLE FILLER)

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LMP)

AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.