

ROOF MEMBRANE

ROOF CAP FLASHING

AIR-SHIELD THRU WALL FLASHING (MIN. 3" (76.2mm) TURNED DOWN CMU) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

AIR-SHIELD LMP (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

BOND BEAM CMU

INSULATED CMU BLOCK

EXTERIOR METAL CLADDING

AIR-SHIELD TRANSITION MEMBRANE (6" (152.4MM) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE)

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOUED W/ BACKER ROD & COMPRESSIBLE FILLER)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.



TITLE:

AIR-SHIELD LMP CMU BU ROOF TIE-IN @ PARAPET
(EXTERIOR METAL CLADDING) (NO INSUL)

SCALE:

NTS

DATE:

DWG NO.:

AS_LMP-76

SEP 7, 2021