



- PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LMP)
- INSULATED CMU BLOCK
- AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)
- AIR-SHIELD THRU WALL FLASHING (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)
- MEL-ROL (MIN. 8" (203.2mm) EXTENDED ABOVE GRADE) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D)
- WEEP BAFFLE
- WEEP, METAL DRIP EDGE COUNTER FLASHING
- POINTING MASTIC (TO SEAL AIR-SHIELD)
- GROUT FILL
- COVE OF BEM SEALANT (FOR TRANSITION) (TO SEAL JOINT)
- MEL-ROL (MIN. 6" (152.4mm) DOWN CLAYTITE) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D)
- MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)
- POINTING MASTIC (TO SEAL MEL-ROL)
- CLAY-TITE (BENTONITE FACING CONCRETE) (TERMINATE W/ TERM BAR)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.