



- PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LMP)
- EXTERIOR BRICK WALL
- INSULATED CMU BLOCK
- POINTING MASTIC (TO SEAL AIR-SHIELD)
- AIR-SHIELD THRU WALL FLASHING (SEAL ALL PENETRATIONS & TERMINATE W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE)
- AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP)
- WEEP BAFFLE
- WEEP, METAL DRIP EDGE COUNTER FLASHING
- GROUT FILL
- HYDRALASTIC 836 (60 MILS) (DETAILING LAYER) (APPLY TO PROPERLY PREPARED SUBSTRATE)
- COVE OF BEM SEALANT (FOR TRANSITION) (TO SEAL JOINT)
- REINFORCING FABRIC HCR (12" (304.8mm) STRIP) (EMBEDDED IN HYDRALASTIC 836)
- HYDRALASTIC 836 (60 MILS) (APPLY TO PROPERLY PREPARED SUBSTRATE)
- MEL-DRAIN (POLY BACKING) (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.