

ROOF MEMBRANE

ROOF CAP FLASHING

EXTERIOR BRICK WALL

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE)

AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

LGMF & BATT INSULATION

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LMP)

EXTERIOR SHEATHING

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOWED W/ BACKER ROD & COMPRESSIBLE FILLER)

VAPOR BARRIER (IF REQ'D)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.



TITLE:

AIR-SHIELD LMP LGMF ROOF TIE-IN @
PARAPET (EXTERIOR BRICK WALL) (NO INSUL)

SCALE:

NTS

DATE:

DWG NO.:

AS_LMP-24

MAR 8, 2018