



ROOF FLASHING
 ROOF MEMBRANE

ROOF COUNTER FLASHING

VAPOR BARRIER (IF REQ'D)

AIR-SHIELD TRANSITION MEMBRANE (MIN. 3" (76.2MM) DOWN WALL) (SEAL ALL PENETRATIONS W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BACKER ROD BELOW FOR DEFLECTION)

AIR-SHIELD LMP (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD LMP)

EXTERIOR SHEATHING

LGMF & BATT INSULATION

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.
 300 INDUSTRIAL DR.
 HAMPSHIRE, IL 60140-0338
 1-800-342-5976



TITLE: AIR-SHIELD LMP LGMF ANGLED ROOF TIE-IN (EXTERIOR BRICK WALL) (NO INSUL)

SCALE: NTS
 DATE: MAR 9, 2018
 DWG NO.: AS_LMP-25