



EXTERIOR SHEATHING

LGMF & BATT INSULATION

AIR-SHIELD LMP (60 MILS WET)  
(MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

POINTING MASTIC (TO SEAL AROUND PENETRATION)

BACKER ROD

AIR-SHIELD TRANSITION MEMBRANE (MIN. 6" (152.4mm) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE)

EXTERIOR BRICK WALL

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

**W. R. MEADOWS INC.**  
 300 INDUSTRIAL DR.  
 HAMPSHIRE, IL 60140-0338  
 1-800-342-5976



TITLE: **AIR-SHIELD LMP LGMF WALL PENETRATION  
(EXTERIOR BRICK WALL) (NO INSUL)**

SCALE: NTS  
 DWG NO.: AS\_LMP-30  
 DATE: AUG 26, 2019