



INSULATED CMU BLOCK

SEALMASTIC TYPE II (30 MILS WET) (MIN. 2" (50.8mm) OVERLAP)

POINTING MASTIC (TO SEAL AIR-SHIELD)

AIR-SHIELD THRU WALL FLASHING (MIN. 6" (152.4mm) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

**W. R. MEADOWS INC.**

300 INDUSTRIAL DR.  
HAMPSHIRE, IL 60140-0338  
1-800-342-5976



TITLE:

SEALMASTIC TYPE II @ CMU BU JAMB (PLANVIEW)

SCALE: DWG NO.:

NTS SM-10

DATE: APR 7, 2022