

CEM-KOTE CW PLUS (2ND LAYER RATE OF 1.4lbs/yd² (.75kg/m²) APPLIED) (TOTAL RATE OF 2.8lbs/yd² (1.5kg/m²) APPLIED) (APPLIED TO PROPERLY PREPARED SURFACE)

CEM-KOTE CW PLUS (1ST LAYER RATE OF 1.4lbs/yd² (.75kg/m²) APPLIED) (APPLIED TO PROPERLY PREPARED SURFACE)

CEM-KOTE FLEX ST (2ND LAYER 31.5 MILS) (APPLIED TO PROPERLY PREPARED SURFACE)

REINFORCING FABRIC HD (EMBEDDED IN CEM-KOTE FLEX)

CEM-KOTE FLEX ST (1ST LAYER 31.5 MILS) (APPLIED TO PROPERLY PREPARED SURFACE)

CEM-KOTE CW PATCH (2" x 2" (50.8mm x 50.8mm) - 2½" x 2½" (63.5mm x 63.5mm) COVE) (APPLY TO PROPERLY PREPARED & SOUND SUBSTRATE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976



TITLE:

**CEM-KOTE CW PLUS SLAB TO WALL TRANSITION
(CEM-KOTE CW PATCH) (CEM-KOTE FLEX ST)**

SCALE:

NTS

DATE:

MAY 12, 2025

DWG NO.:

CKOTE-24