

AIR-SHIELD STPE (60 MILS WET)
(MIN. 3" (76.2mm) OVERLAP) (APPLY TO
PROPERLY PREPARED SUBSTRATE)

AIR- SHIELD BUTYL FLASHING (MIN.
6" (152.4mm) STRIP CENTERED) (SEAL ALL
PENETRATIONS W/ BEAD OF POINTING
MASTIC) (APPLY TO PRIMED SURFACE)

EXTERIOR BRICK WALL

INSULATED CMU BLOCK

PRE-INSTALLED MASONRY ANCHOR
(SEALED W/ AIR-SHIELD STPE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST
BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R.
MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338

1-800-342-5976



TITLE:

AIR-SHIELD STPE CMU BU EXTERNAL CORNER
(EXTERIOR BRICK WALL) (NO INSUL) (PLANVIEW)

SCALE:

NTS

DATE:

NOV 10, 2025

DWG NO.:

AS_STPE-17