



ROOF CAP FLASHING

ROOF MEMBRANE (MIN. 3" (76.2mm) OVERLAP)

AIR-SHIELD STPE (60 MILS WET) (APPLY TO PROPERLY PREPARED SUBSTRATE)

EXTERIOR BRICK WALL

INSULATED CMU BLOCK

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD STPE)

AIR-SHIELD STPE (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

AIR- SHIELD BUTYL FLASHING (MIN. 12" (304.8mm) STRIP) (MIN. 3" (76.2mm) EXTENDED DOWN CMU) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOWED W/ BACKER ROD & COMPRESSIBLE FILLER)

AIR-SHIELD STPE (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.
 300 INDUSTRIAL DR.
 HAMPSHIRE, IL 60140-0338
 1-800-342-5976



TITLE: AIR-SHIELD STPE CMU BU ROOF TIE-IN @ PARAPET (EXTERIOR BRICK WALL) (NO INSUL) COND.2

SCALE: NTS
 DATE: NOV 10, 2025
 DWG NO.: AS_STPE-28