



ROOF CAP FLASHING

ROOF MEMBRANE (MIN. 3" (76.2mm) OVERLAP)

AIR-SHIELD STPE (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

LGMF & BATT INSULATION

EXTERIOR SHEATHING

EXTERIOR BRICK WALL

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD STPE)

AIR- SHIELD BUTYL FLASHING (MIN. 3" (76.2mm) EXTENDED ONTO SHEATHING) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOWED W/ BACKER ROD & COMPRESSIBLE FILLER)

VAPOR BARRIER (IF REQ'D)

AIR- SHIELD BUTYL FLASHING (MIN. 3" (76.2mm) EXTENDED ONTO SHEATHING) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOWED W/ BACKER ROD & COMPRESSIBLE FILLER)

AIR-SHIELD STPE (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.