



EXTERIOR BRICK WALL

EXTERIOR SHEATHING

LGMF & BATT INSULATION

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD STPE)

AIR-SHIELD STPE (60 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

WEEP Baffle

POINTING MASTIC (TO SEAL MEL-ROL) (TO SEAL AIR-SHIELD)

MEL-ROL (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D)

AIR- SHIELD BUTYL FLASHING (EXTEND MIN. 3" (76.2mm) PASS MEL-ROL) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

WEEP, METAL DRIP EDGE COUNTER FLASHING

DETAIL STRIP OR MEL-ROL STRIP (EXTEND MIN. 3" (76.2mm) TURNED UP WALL) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

COVE OF BEM SEALANT (FOR TRANSITION) (TO SEAL JOINT)

DETAIL STRIP OR MEL-ROL STRIP (EXTEND MIN. 3" (76.2mm) TURNED DOWN MEL-ROL) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION)

MEL-ROL (APPLY MEL-PRIME TO SURFACE PRIOR TO APPLICATION) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D)

MEL-DRAIN (FABRIC FACING EARTH) (TERMINATE W/ TERM BAR IF REQ'D)

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.