

ROOF MEMBRANE

ROOF CAP FLASHING

AIR- SHIELD BUTYL FLASHING (MIN. 3" (76.2mm) TURNED DOWN CMU) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (TERMINATE W/ TERM BAR & BEAD OF POINTING MASTIC IF REQ'D) (APPLY TO PRIMED SURFACE)

AIR-SHIELD STPE (27 MILS WET) (MIN. 3" (76.2mm) OVERLAP) (APPLY TO PROPERLY PREPARED SUBSTRATE)

BOND BEAM CMU

INSULATED CMU BLOCK

PRE-INSTALLED MASONRY ANCHOR (SEALED W/ AIR-SHIELD STPE)

AIR- SHIELD BUTYL FLASHING (6" (152.4MM) STRIP CENTERED) (SEAL ALL PENETRATIONS W/ POINTING MASTIC) (APPLY TO PRIMED SURFACE)

AIR- SHIELD BUTYL FLASHING (MIN. 6" (152.4mm) STRIP) (SEAL ALL PENETRATIONS W/ BEAD OF POINTING MASTIC) (APPLY TO PRIMED SURFACE) (BELLOWED W/ BACKER ROD & COMPRESSIBLE FILLER)

EXTERIOR BRICK WALL

NOTE: DETAIL IS A GUIDE FOR INSTALLATIONS OF W. R. MEADOWS PRODUCTS ONLY. DETAIL MUST BE REVIEWED AND VERIFIED BY A DESIGN PROFESSIONAL FOR SUITABILITY ON THE PROJECT. W. R. MEADOWS DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING.

W. R. MEADOWS INC.

300 INDUSTRIAL DR.
HAMPSHIRE, IL 60140-0338
1-800-342-5976



TITLE:

AIR-SHIELD STPE CMU BU ROOF TIE-IN @
PARAPET (EXTERIOR BRICK WALL) (NO INSUL)

SCALE:

NTS

DATE:

DWG NO.:

AS_STPE-27

NOV 10, 2025